




NFPA Rating



HMIS Rating

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	1
PERSONAL PROTECTION	G

Material Safety Data Sheet

INNOTECH CURE AND SEAL SB:

Gloss and Matte finish – Low VOC

Revision Date: 04/20/2010

Page No.: 1 of 6

Version: 1

File Name: MSDS Cure and Seal

1. SUBSTANCE/PREPARATION AND COMPANY IDENTIFICATION:

Company: Innotech Decorative Concrete Products, 2055 Enterprise Parkway, Twinsburg, OH 44087, 877.829.7880

24-Hour Emergency Response Information, CHEMTREC: 800.424.9300

Chemical Family: Paint, Synonyms: Flammable Liquid

2. COMPOSITION/INFORMATION ON INGREDIENTS:

Table with 3 columns: CAS NO., CHEMICAL NAME, EXPOSURE LIMITS. Rows include Proprietary, Trade secret, 540-88-5, 67-64-1.

3. HAZARD IDENTIFICATION:

Routes of Exposure: Inhalation, Ingestion, eyes, and Skin.

Health Hazards:

Acute: May cause eye, skin, gastrointestinal, and lung irritation. Chronic: Prolonged and repeated exposures to high concentrations may cause hearing loss. Exposure to toluene may affect the developing fetus.

Skin Contact: May cause irritation and redness. Prolonged or repeated exposure can cause defatting and drying of the skin.

Eye Contact: May cause redness, tearing, and irritation of the eyes. Direct contact may cause permanent eye damage.

Inhalation: May cause headache, nausea, dizziness, and loss of coordination. Continued inhalation may result in unconsciousness and death.

Ingestion: May be harmful if swallowed. Aspiration of the material into the lungs can cause chemical pneumonitis, which can be fatal.

Carcinogen: Contains trace amounts of Naphthalene (0.67-1.33% by wt.), which has been shown by the NTP to be carcinogenic.

4. FIRST-AID MEASURES:

Skin: Clean material from skin with acetone, and then wash with soap and water followed by moisturizer.

Eyes: Flush with a gentle but large stream of clean water for 15 minutes, lifting the lower and upper eyelids occasionally. Call a physician if irritation persists.

Inhalation: Move to fresh air and provide oxygen if breathing is difficult. Seek medical attention.

Ingestion: DO NOT INDUCE VOMITING. Give large quantities of water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES:

Flash Point (TCC): 76 °F

Flammable Limits(% volume in air): LEL=1.1 UEL=12.8

Extinguishing Media: Dry chemical, CO₂, alcohol-resistant foam

Special Fire Fighting Procedures: Evacuate area and fight fire from a distance. Firefighters wear NIOSH approved self-contained breathing apparatus. Cool containers exposed to fire with water. Vapors are heavier than air and may travel along the ground to distant ignition sources.

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions:

Contain spill and absorb. Keep product from entering storm drains. Use recommended personal protective clothing and equipment. Equipment used when handling this product must be grounded.

Environmental precautions:

Follow all Federal, State and Local regulations when storing and disposing of substances. Do not allow material to run off work area, excess material should be absorbed or vacuumed and disposed of in accordance with regulations. Consult local and federal guidelines for proper disposal of these materials.

Waste Disposal Method: Liquid material is an ignitable waste (D001). Dispose of material in accordance with federal, state, and local guidelines

7. HANDLING and STORAGE:

Normal Handling: Always use good industrial hygiene practices and safety guidelines.

Storage: Store material in its original container. Keep containers tightly closed when not in use. Keep material away from open flame, sparks, or other sources of heat and ignition.

Waste Disposal Method: Liquid material is an ignitable waste (D001). Dispose of material in accordance with federal, state, and local guidelines.

Special Precautions: Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld on or near the containers.

Shelf Life:

12 months

8. EXPOSURE CONTROLS and PERSONAL PROTECTION:

Respiratory Protection: Use a NIOSH-approved organic vapor respirator when exposure level cannot be maintained below limits.

Ventilation: Provide adequate mechanical ventilation to keep exposure levels below TLV's.

Protective Gloves: Wear impervious chemical gloves.

Eye Protection: Wear chemical safety glasses.

Other Protective Clothing or Equipment: As needed to prevent repeated/prolonged contact.

Work/Hygienic Practices: Use only in adequately-ventilated area unless recommended respiratory protection is used. Wash thoroughly with soap and water after handling and before eating, smoking, or using washroom. If clothes become contaminated, change to clean clothing and wash contaminated clothes before re-use.

9. PHYSICAL and CHEMICAL PROPERTIES:

Form:	Liquid
Odor:	Acetate
Color:	Clear
pH value:	Unspecified
Total solids/Non-volatiles:	<25
Total VOC:	<350 g/l
Specific gravity:	0.82 (H ₂ O = 1)
Boiling point:	323 °F (161.7 °C)
Vapor density:	Heavier than air
Vapor pressure:	Unknown
Evaporation Rate:	Slower than Ether
Solubility in water:	Immiscible

10. STABILITY and REACTIVITY:

Reactivity: Stable

Conditions to avoid: Prevent vapor accumulation. Avoid heat and flames.

Incompatibility (Materials to Avoid): Strong oxidizers.

Hazardous Decomposition (Byproducts): Carbon monoxide and carbon dioxide.

Hazardous Polymerization: Should not occur.

11. TOXICOLOGY INFORMATION:

SARA 311/312:

Acute Health Hazard

Fire Hazard

Chronic Health Hazard

SARA 313:

Components

See Section III (Aromatic Naphtha components)

12. ECOLOGICAL INFORMATION:

Biodegradation:

Test method: Unspecified

Analysis method: Unspecified

Degree of elimination: Unspecified

Environmental toxicity:

Acute and prolonged toxicity to fish: Unspecified

Toxicity to microorganisms: Unspecified

Other ecotoxicological advice: Unspecified

13. DISPOSAL CONSIDERATIONS:

Waste disposal of substance:

Liquid material is an ignitable waste (D001). Dispose of material in accordance with federal, state, and local guidelines.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

Special Precautions:

Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld on or near the containers.

RCRA:

Unspecified.

14. TRANSPORTATION INFORMATION:

Land transportation:

US DOT Shipping Class: Paint, 3, UN1263, PGII

Sea transportation:

IMDG: Unspecified

Air transportation:

IATA/ICAO: Unspecified

15. REGULATORY INFORMATION:

Federal Regulations:

Registration status:

TSCA, US :

Unspecified

OSHA hazard category:

Hazardous

SARA hazard category (EPCRA 311/312):

Acute health hazard, Fire Hazard, Chronic Health Hazard

California Proposition 65: Naphthalene (91-20-3)

0.67-1.33%

CA_65 C

**Material Safety Data Sheet
Innotech Cure and Seal**

Revision Date: 4/20/2010
Version: 1

Page No.: 6 of 6
File Name: *MSDS Cure and Seal*

16. OTHER INFORMATION:

NFPA Rating:

Health: 2 Fire: 3 Reactivity: 0 Special Hazard: none

HMIS III Rating:

Health: 2 Flammability: 3 Physical Hazard: 1
Personal Protection: G

Both NFPA and HMIS III rating systems use a numbering scale that ranges from 0 to 4 to indicate the degree of hazard. A value of zero means the substance possesses no hazard while a value of four indicates high hazard.

HMIS III personal protection ratings A-K are specified by HMIS, while this manufacturer specifies ratings L-Z please review section 8 for specific safety equipment recommended for use with this product.

Reason for Revision:

New Product Document

Reviewed:

04/20/2010

Local Contact Information:

Innotech Decorative Concrete Products
877.829.7880 (8 a.m. to 5 p.m., M-F, EST)
www.innotechdcp.com

24-Hour Emergency Response Information:

CHEMTREC: 800.424.9300

Notice: While the descriptions, information, and data contained in this document are presented in good faith and believed to be accurate, it is provided only to guide the user. Many factors may affect processing or application/use, Innotech recommends user-tests to determine suitability for a particular purpose, prior to use. In no case shall the descriptions, information, or data contained in this document be considered a part of the Innotech terms/conditions of sale. Further, the user expressly understands and agrees that Innotech assumes no obligation or liability for the descriptions, information, or data, or the results obtained, as all such being given and accepted at users own risk.

Warranty: This is a proprietary INNOTECH product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over product use, no warranty is made as to the effects of such use (neither expressed nor implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact INNOTECH with any questions regarding this policy. *Innotech is a registered tradename of CHROMASYSTEMS LLC, an Ohio company.*

Innotech Decorative Concrete Products is a registered tradename of ChromaSystems LLC, a wholly owned part of the ChromaScape family of companies. For more information, go to www.chromascape.com. ©2009 CHROMASYSTEMS, LLC.

END OF DATA SHEET