

# Safety Data Sheet



## Innotech Solid Color Sealer Stain

### Section 1 Product Description

Recommended Use: Coloring and Sealing decorative concrete  
Supplier: ChromaScape Inc. 2055 Enterprise Pkwy. Twinsburg OH 44087 330-998-7574  
Emergency Phone: Chemtrec: 1-800-424-9300

### Section 2 Hazard identification

Category 3 Flammable Liquid  
Category 3 Acute Inhalation Toxicity  
Category 2 Carcinogen  
Category 2A Eye Irritation  
Category 2 Skin Irritation  
Category 1B Germ Cell Mutagenicity  
Category 1B Reproductive Toxicity  
Category 3 Specific Target Organ Acute Toxicity (respiratory system, central nervous system)  
Category 2 Specific Target Organ Chronic Toxicity (liver, kidney, central nervous system)  
Category 2 Acute Aquatic Toxicity



Signal Word:

Danger

Hazard Statements:

H226 Flammable liquid and vapor  
H315 Causes skin irritation  
H319 Causes serious eye irritation  
H331 Toxic if inhaled  
H335 May cause respiratory irritation  
H336 May cause drowsiness or dizziness  
H340 May cause genetic defects  
H351 Suspected of causing cancer  
H360 May damage fertility or the unborn child  
H371 May cause damage to liver, kidney, and central nervous system through prolonged or repeated exposure  
H401 Toxic to aquatic life

Precautionary statements:

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking  
P233 Keep container tightly closed  
P260 Do not breathe mist/vapors/spray  
P264 Wash skin thoroughly after handling  
P271 Use only outdoors or in a well-ventilated area  
P281 Use personal protective equipment as required

# Safety Data Sheet

## Response:

P301+P312+P331 IF SWALLOWED: Do NOT induce vomiting. Immediately call a poison center or doctor/physician if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs, get medical advice/attention

P370+P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction

## Storage:

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## Disposal:

P501 Dispose of contents/container in accordance with local/federal regulations.

## Section 3 Composition/ Information on Ingredients

	<u>CAS #</u>	<u>OSHA PEL(TWA)</u>	<u>ACGIH(TLV-TWA)</u>	<u>Conc.(wt. %)</u>
Acrylic Polymer	Proprietary	Not established	Not established	15.0 – 20.0
Solvent Naphtha, Light	64742-95-6	Not established	Not established	30.0 – 51.0
bis(2-Ethylhexyl) phthalate	117-81-7	5 ppm	5 ppm	0.2 – 0.5
Solvent Naphtha	Proprietary	17 ppm	5 mg/m <sup>3</sup>	4.1 – 4.6
Benzene, trimethyl	25551-13-7	25 ppm	25 ppm	25.4 – 30.5
1,2,4-Trimethylbenzene	95-63-6	25 ppm(1989 std.)	25 ppm	15.2 – 20.5
Cumene	98-82-8	50 ppm	50 ppm	2.5 – 5.1
Naphthalene	91-20-3	10 ppm	10 ppm	0.0 – 0.2
Mixed xylene isomers	1330-20-7	100 ppm	100 ppm	0.5 – 3.5
Toluene	108-88-3	200 ppm	50 ppm	0.0 – 0.6
Cymenes	25155-15-1	Not established	Not established	0.5 – 0.8

## Section 4 First Aid Measures

### Emergency First Aid Procedures

**Skin:** Clean material from skin with acetone, then wash with soap and water followed by moisturizer. If irritation persists, contact a physician.

**Eyes:** Flush with a gentle but large stream of clean water for 15 minutes, lifting the lower and upper eyelids occasionally. Remove contact lenses if able. Call a physician if irritation persists.

**Inhalation:** Move to fresh air and provide oxygen if breathing is difficult. Seek medical attention.

**Ingestion:** DO NOT INDUCE VOMITING. Give large quantities of water. Do not give milk or alcoholic beverages. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

## Section 5 Firefighting Procedures

**Suitable Extinguishing Media:** Dry chemical, CO<sub>2</sub>, alcohol-resistant foam

**Unsuitable Extinguishing Media:** High-volume water jet

**Flash Point (TCC):** 105° F

**Flammable Limits (% volume in air for solvents):** LEL=1.0 UEL=7.0

**Special Fire Fighting Procedures:** Evacuate area and fight fire from a distance. Firefighters wear NIOSH approved self-contained breathing apparatus. Cool containers exposed to fire with water. Vapors are heavier than air and may travel along the ground to distant ignition sources. Do not allow runoff from firefighting to enter drains or water courses.

## Section 6 Spill or Leak Procedures

**Steps to Take if Material is Released or Spilled:** No health effects expected from the clean-up of the material if contact can be avoided. Follow the protection information found in Section 8 of this SDS. Ventilate the contaminated area. Prevent the spread of spilled material by using a suitable absorbent material or sand dam.

## Section 7 Handling and Storage

**Normal Handling:** Always use good industrial hygiene practices and safety guidelines.

# Safety Data Sheet

**Storage:** Store material in its original container. Keep containers tightly closed when not in use. Keep material away from open flame, sparks, or other sources of heat and ignition.

**Waste Disposal Method:** Liquid material is an ignitable waste (D001). Dispose of material in accordance with federal, state, and local guidelines.

**Special Precautions:** Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld on or near the containers.

## Section 8 Protection Information

**Respiratory Protection:** Use NIOSH-approved organic vapor respirator when exposure levels can't be kept below limits.

**Ventilation:** Provide adequate mechanical ventilation to keep exposure levels below TLV's.

**Protective Gloves:** Wear impervious chemical gloves.

**Eye Protection:** Wear chemical safety glasses.

**Other Protective Clothing or Equipment:** As needed to prevent repeated/prolonged contact.

**Work/Hygienic Practices:** Use only in adequately-ventilated area unless recommended respiratory protection is used. Wash thoroughly with soap and water after handling and before eating, smoking, or using washroom. If clothes become contaminated, change to clean clothing and wash contaminated clothes before re-use.

## Section 9 Physical Data

**Appearance:** Opaque colored liquid

**Odor:** Aromatic

**Odor Threshold:** No data available

**pH:** None

**Freezing/Melting Point:** -63° F

**Boiling Point:** 300° F

**Flash Point:** 105° F

**Evaporation Rate:** 0.9 (butyl acetate = 1)

**Flammability (solid, gas):** No data available

**Lower/Upper Flammability:** 1.0 – 7.0

**Vapor Pressure:** 2.1 mm Hg at 20° C

**Vapor Density:** 3.5 (air=1)

**Density:** 1.11 g/cc

**Solubility:** Negligible

**Partition Coefficient:** No data available

**Auto-ignition Temperature:** 865° F

**Decomposition temperature:** No data available

**Viscosity:** 20 - 30 centipoise

## Section 10 Reactivity Data

**Reactivity:** Stable

**Conditions to avoid:** Prevent vapor accumulation. Avoid heat and flames.

**Incompatibility (Materials to Avoid):** Strong oxidizers, acids, alkalies, nitrates.

**Hazardous Decomposition (Byproducts):** Carbon monoxide and carbon dioxide.

**Hazardous Polymerization:** Should not occur.

## Section 11 Toxicity Data

**Routes of Exposure:** Inhalation, Ingestion, eyes, and Skin.

**Acute Toxicity Lethal Doses (ATE):**

LC50 (inhl) 8.7 mg/l

LD50 (oral) 7564 mg/kg

LD50 (skin) 7880 mg/kg

**Health Hazards:**

**Acute:** May cause eye, skin, and lung irritation. May cause central nervous system depression, causing drowsiness and dizziness.

**Chronic:** Prolonged and repeated exposures to high concentrations may cause damage to central nervous system, liver, kidneys.

**Skin Contact:** May cause irritation and redness. Prolonged or repeated exposure can cause defatting and drying of the skin which may result in a burning sensation and a dried, cracked appearance.

**Eye Contact:** Causes redness, tearing, irritation of the eyes. Direct contact will cause serious eye irritation.

**Inhalation:** May cause headache, nausea, dizziness, and loss of coordination. Continued inhalation may result in unconsciousness.

# Safety Data Sheet

**Ingestion:** May cause gastrointestinal irritation. Aspiration of the material into the lungs can cause chemical pneumonitis, which can be fatal.

**Carcinogen:** Contains Naphthalene (0.0-0.2% w/w), bis(2-Ethylhexyl) phthalate (0.2 – 0.5% w/w), Light Solvent Naphtha (30.0 – 51.0% w/w), and Cumene (2.5 – 5.1% w/w), which are IARC category 2B possible carcinogen.

**Aggravation of Pre-existing Conditions:** Persons with pre-existing skin, eye, or lung disorders may be more susceptible to the effects of the substance.

## Section 12 Ecological Data

**Acute Toxicity to Fish:** LC50 (96 hr) 8.3 mg/L (Calculated)

**Acute Toxicity to Aquatic Invertebrates:** EC50 (48 hr) 3.1 mg/L (Calculated)

**Toxicity to Aquatic Plants:** EC50 algae 3.1 mg/L (Calculated)

**Toxicity to Microorganisms:** High concentrations may be harmful to sewage treatment plant microbes.

**Chronic Toxicity to Fish:** No data available

**Chronic Toxicity to Aquatic Invertebrates:** No data available

**Persistence and Degradability:** Expected to degrade readily and rapidly in the presence of oxygen

**Bioaccumulation Potential:** This material is not expected to bioaccumulate.

**Mobility in the Soil:** Expected to move slowly in soil and water.

**Other Adverse Effects:** No data available.

## Section 13 Disposal Information

**Waste Disposal Method:** Liquid material is an ignitable waste (D001). Dispose of material in accordance with all Federal, State, and Local regulations.

## Section 14 Transport Information

**Domestic USDOT:** Non-Regulated Material in containers <119 gallons

**IMO/IATA:**

**Proper Shipping Name:** PAINT

**Hazard Class:** 3

**UN:** UN1263

**Packing Group:** PGIII

**Marine Pollutant:** No

## Section 15 Regulatory Information

**SARA 311/312:** Yes. (Fire, Acute, Chronic).

**OSHA:** This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200).

**TSCA:** Components of this material are listed or are exempt from the EPA TSCA Inventory of Chemical Substances.

**California Proposition 65:** WARNING! This product contains a chemical known to the State of California to cause cancer.

71-43-2 Benzene  
98-82-8 Cumene  
91-20-3 Naphthalene

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

71-43-2 Benzene  
117-81-7 bis(2-Ethylhexyl) phthalate  
108-88-3 Toluene

<b>Massachusetts Right To Know:</b>	25551-13-7	Benzene, trimethyl	25.4 – 30.5
	91-20-3	Naphthalene	0.0 – 0.2
	95-63-6	1,2,4-Trimethylbenzene	15.2 – 20.5
	98-82-8	Cumene	2.5 – 5.1
	1330-20-7	Mixed xylene isomers	0.5 – 3.5
	108-88-3	Toluene	0.0 – 0.6

<b>Pennsylvania Right To Know:</b>	64742-94-6	Light Solvent Naphtha	30.0 – 51.0
	25551-13-7	Benzene, trimethyl	26.4 – 30.5
	Proprietary	Solvent Naphtha	4.1 – 4.6
	91-20-3	Naphthalene	0.0 – 0.2
	95-63-6	1,2,4-Trimethylbenzene	15.2 – 20.5
	98-82-8	Cumene	2.5 – 5.1

## Safety Data Sheet

	1330-20-7	Mixed xylene isomers	0.5 – 3.5
	108-88-3	Toluene	0.0 – 0.6
<b>New Jersey Right To Know:</b>	64742-94-6	Light Solvent Naphtha	30.0 – 51.0
	25551-13-7	Benzene, trimethyl	26.4 – 30.5
	Proprietary	Solvent Naphtha	4.1 – 4.6
	91-20-3	Naphthalene	0.0 – 0.2
	95-63-6	1,2,4-Trimethylbenzene	15.2 – 20.5
	98-82-8	Cumene	2.5 – 5.1
	1330-20-7	Mixed xylene isomers	0.5 – 3.5
	108-88-3	Toluene	0.0 – 0.6
	25155-15-1	Cymenes	0.5 – 0.8

### Section 16 Additional Information

**The regulatory information provided is not intended to be comprehensive. Other Federal, State and Local regulations may apply to this material.**

The information on this SDS is provided in good faith in the interest of product safety and believed to be accurate to the best of our knowledge. However, ChromaScape makes no guarantee and assumes no liability for the data contained. Users should conduct their own research regarding suitability for their purposes. Nothing contained in this SDS should be misconstrued as permission to violate any regulation. End users should follow all local, state, national and international regulations as apply.