

# Solid Color Stain Sealer

INNOTECH<sup>®</sup> SOLID COLOR STAIN SEALER is an acrylic resin stain formulated specifically for concrete. This product is available in 42 standard colors from the INNOTECH COLOR HARDENER color chart. When applied properly, it resists oils, detergents, acids, salts and other types of chemicals. INNOTECH SOLID COLOR STAIN SEALER dust-proofs and aids in clean-up. INNOTECH SOLID COLOR STAIN SEALER is a pure acrylic which will provide longer lasting results on cured concrete. INNOTECH SOLID COLOR STAIN SEALER is intended to be used on fully-cured concrete that has been cleaned and properly prepared to receive INNOTECH SOLID COLOR STAIN SEALER.

## Product Features and Benefits

### **INNOTECH SOLID COLOR STAIN SEALER...**

- Penetrates the surface for a good bond.
- Is quick drying.
- Is water resistant.
- Resists most oils and greases.
- Provides a uniform finished appearance.
- Seals and protects the treated surface.
- Rejuvenates old concrete.
- Creates opacity that aids in hiding “undesirable” appearances.

## Required Tools & Materials

- An airless sprayer or roller for application.
- Synthetic-Bristle Brush (as needed to cut in tight areas).
- Absorbent Cloth or Small Container to Catch Drips.
- Painters Tape and Plastic Sheeting.
- An aromatic solvent such as A100 solvent or Xylene for clean up.

## Prior to Application

Surfaces must be cleaned and degreased prior to application of INNOTECH SOLID COLOR STAIN SEALER with INNOTECH CONCRETE DEGREASER & NEUTRALIZER<sup>†</sup>. Rinse substrate thoroughly and allow 24 hours to dry completely. On extremely smooth or burnished concrete, a light profiling of the substrate may be necessary to achieve proper surface adhesion. Always apply a small sample in an inconspicuous place to ensure both color and compatibility to substrate is acceptable.

## Product Application

- **Always create an actual finished mock-up sample for client approval prior to installation of each project.**
- Apply with an airless sprayer or roller for best results.
- Brushes can be used to “cut in” tight areas.
- One coat will provide an opaque finish while, a second coat will add additional gloss.
- For garage floors or other interior finishes it is recommended that INNOTECH INTERIOR FLOOR FINISH<sup>†</sup> or INNOTECH NATURAL BEAUTY<sup>†</sup> be applied as a protective maintenance coating to protect against scratching.

## Maintenance

- Develop and follow a schedule of routine maintenance for all colored concrete so it maintains a quality appearance. Installations should be routinely inspected, cleaned and resealed as required by the local conditions. All installations should be maintained on a routine basis with the use of INNOTECH maintenance products to ensure the preservation of a high-quality long-lasting surface. Cleaning and resealing schedules will depend on a number of factors including, but not limited to, volume and intensity of wear, and maintenance procedures. All installations should be maintained on a routine basis with the use of INNOTECH maintenance products to ensure the preservation of a high-quality long-lasting surface.
- For garage floors or other interior finishes it is recommended that INNOTECH INTERIOR FLOOR FINISH<sup>†</sup> or INNOTECH NATURAL BEAUTY<sup>†</sup> be applied as a protective maintenance coating to protect against scratching.

## Product Limitations

- Should not be used on concrete that is to receive a bonded topping.
- Rubber wheeled tires may leave marks.
- Do not over-apply.
- Apply only when surface and air temperatures are between 50 °F and 90 °F.
- Do not use caustic, corrosive, citrus-based or ammonia cleaners. (pH neutral cleaners are recommended for cleaning).
- Gasoline and hot solvents will melt the sealer stain.

### **NOTE:**

Gasoline and other auto parts cleaners containing hot solvents will melt stain. Wiping will smear the stain. Allow to dry, clean and recoat affected area for best appearance. If area that is to be treated with INNOTECH SOLID COLOR STAIN SEALER is to be regularly exposed to chemicals, it is highly recommended that the area be spot tested to ensure compatibility and resistance to said chemicals before proceeding. INNOTECH SOLID COLOR STAIN SEALER contains flammable solvents. Provide adequate ventilation and avoid sparks and open flame. Continue to ventilate area after installation until all vapors have been removed.

## Technical Data

---

Refer to corresponding MSDS prior to use.

- VOC: <600 g/L
- Flash Point: 105 °F
- Finish: semi-gloss

## Available Packaging and Coverage Information

---

Packaging: INNOTECH SOLID COLOR STAIN SEALER is available in 1- and 5-gallon containers.

**Coverage rates may vary depending on the texture, porosity and condition of the concrete, application method, and other local conditions.**

- Coverage is approximate and is as follows by surface type:

<u>Finish</u>	<u>1st Coat, per Sq.Ft.</u>	<u>2nd Coat, per Sq.Ft.</u>
Broom finished	200	250
Stamped concrete	200	250
Smooth trowel	250	300
Block	100	150

## Product Shelf Life/Storage

---

INNOTECH SOLID COLOR STAIN SEALER should be stored indoors, away from heat or direct sunlight. Do not store below 40 °F. If the Liquid freezes, discard. Shelf life: 12 months.

## Product Handling

---

Prior to using INNOTECH SOLID COLOR STAIN SEALER please reference the corresponding Material Safety Data Sheet to ensure safe handling.

## Warranty


---

INNOTECH SOLID COLOR STAIN SEALER is a proprietary product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over the product use, no warranty is made as to the effects of such use (neither expressed nor implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product.

---

**†PLEASE REFER TO CORRESPONDING TECHNICAL BULLETIN FOR PRODUCT AND APPLICATION DATA.**

INNOTECH SOLID COLOR STAIN SEALER and other INNOTECH products are for professional use only.

 Innotech Decorative Concrete Products is a member of the ChromaScape family of brands.

For more information, visit [www.chromascape.com](http://www.chromascape.com). ©2012 ChromaScape, Inc.

1.5M

08.12

INNOTECH products can be purchased at:



INNOTECH Decorative Concrete Products  
Customer Service 877-829-7880 or 330-425-2506  
Fax 330-425-2466  
[CustomerService@InnotechDCP.com](mailto:CustomerService@InnotechDCP.com)  
[www.InnotechDCP.com](http://www.InnotechDCP.com)